



## DT-380 DIGITAL COMPACT AC CLAMP METER

The CEM DT-380 comes with all the rugged, reliable and accurate features you trust, in a small, ergonomic design. The innovative body design offers a more compact tool to meet your needs. With features of AC current measurements up to 400 A, a large 30 mm jaw opening and CAT III 600V safety rating, you get an easy-to-use tool that handles your everyday electrical maintenance needs.

The meter confirms to EN-61010-1, EN-61326. The instrument houses a Non-Contact Voltage Detector to show the presence of live wire. The Flashlight in the clamp jaw and the backlit display helps easy access in dark and tight areas.

### FEATURES

- 3-1/2 Digits 1999 Counts Backlit LCD Display
- Non Contact Voltage Detector Built-in
- Flashlight in the clamp to access dark areas
- Single Hand Easy Operation
- Full Overload Protection
- Data Hold Function to Freeze the display
- AC Voltage & Current Bandwidth 50 to 60Hz
- Diode Test and Audible Continuity Test
- Low Battery and Overload Indication
- Temperature Measuring Facility with K type thermocouple
- AC/DC Voltage and AC Current measuring facility
- Resistance measurement
- Clamp Jaw Dia of 30mm
- Operating Temperature: 5 to 40°C (41°F to 104°F)
- Storage Temperature: -20 to 60°C (-4°F to 140°F)
- Operating Humidity: Max 80% up to 31°C decreasing linearly to 50% at 40°C
- Storage Humidity < 80% RH
- Operating Altitude 7000 ft
- 2 x 1.5V AAA Battery Operated
- Size: 230 x 82 x 40 mm / Weight: 230g.
- Safety: IEC 61010-1, CAT III 600V, CE

## SPECIFICATIONS

Function	Range	Resolution	Accuracy
AC Current (50 to 60Hz)	20A	0.01A	± (2.5 % ± 5 Digits)
	200A	0.1A	
	400A	1A	± (3.0 % ± 5 Digits)

Function	Range	Resolution	Accuracy
DC Voltage	200mV	0.1mV	± (1.5 % ± 2 Digits)
	2V	0.001V	
	20V	0.01V	
	200V	0.1V	± (2.0 % ± 2 Digits)
	600V	1V	

Input Protection: 600V DC.

Function	Range	Resolution	Accuracy
AC Voltage (50Hz to 60Hz)	200mV	0.1mV	± (1.5 % ± 10 Digits)
	2V	0.001V	± (1.5 % ± 8 Digits)
	20V	0.01V	
	200V	0.1V	
	600V	1V	± (2.5 % ± 8 Digits)

Input Protection: 600V AC RMS.

Function	Range	Resolution	Accuracy
Resistance	200Ω	0.1Ω	± (1.0 % ± 4 Digits)
	2 KΩ	0.001 KΩ	± (1.5 % ± 4 Digits)
	20 KΩ	0.01 KΩ	
	200 KΩ	0.1 KΩ	
	2 MΩ	1 KΩ	± (2.5 % ± 4 Digits)
	20 MΩ	10 KΩ	± (3.5 % ± 4 Digits)

Input Protection: 250V DC or 250V AC RMS.

Function	Range	Resolution	Accuracy
Temperature (type-K) (probe accuracy not included)	-20 to 760°C	1°C	± (3 % ± 5 Digits)
	-4 to 1400°C	1°F	

Input Protection: 250V DC or 250V AC RMS.

Function	Testing Condition	Reading
Diode	Forward DCA is approx.0.3mA, open circuit Voltage MAX . 1.5V	Forward voltage drop of Diode
Continuity	Open Voltage is approx 0.5V	Buzzer makes a long sound, While resistance is less than (50Ω)

Input Protection: 250V DC or 250V AC RMS.

## INCLUDED ACCESSORIES:

- Carrying Case
- Testing Leads
- Temperature Probe
- Battery
- Instruction Manual
- Test Certificate