



The compact and handy base model was specifically designed for indoor applications. Shortcut and Soft grip keys for addition, subtraction, area and volume calculation make measuring fast and very reliable.

Usage

Measuring distances
Computing functions, e. g. areas and volumes

Laser Classification

The CEM produced a visible laser beam which emerges from the front of the instrument.
Laser Class 2



LDM-65 LASER DISTANCE METER

- | Laser used for showing the target measured
- | Area measurement
- | Volume measurement
- | Single measurement mode
- | Continuous measurement mode
- | Max/Min measurement records
- | Backlit LCD Display
- | Addition and Subtraction of distances
- | Indirect measurements can be done
- | 20 Data records

LDM-65

Laser Distance Meter



Technical Specifications

Range	0.05 to 65m* (0.15 ft. to 213.2 ft.*)
Measuring accuracy up to 10m (2 σ , standard deviation)	Typically : ± 1.5 mm** (± 0.06 in**)
Measuring Units	m, in, ft
Smallest Unit Displayed	1 mm
Laser Class	Class II
Laser Type	635 nm, <1mW
Area, Volume Calculations	✓
Indirect measurement using Pythagoras	✓
Addition / Subtraction	✓
Continuous Measurement	✓
Min/Max Distance Tracking	✓
Display illumination and multi-line display	✓
Beep indication	✓
Dust Protect/Splash Proof	IP 54
History measurement records	20
Keyboard Type	Super Soft-Touch (Long life)
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-10°C to 60°C (14°F to 140°F)
Battery Life	up to 4,000 measurements
Batteries	Type AAA 2 x 1.5V
Auto laser switch-off	after 0.5 min
Auto instrument switch-off	after 3 min
Dimension	115 x 48 x 28 mm
Weight	135g

Accessories

Battery, Carrying Case,
Instruction Manual and Test
Certificate.

Contact :

CEM INSTRUMENTS (INDIA) PVT. LTD.

32A, Ganesh Chandra Avenue, 4th Floor, Kolkata-700013
Tel: 033-22151376, 22159759
Email: info@cem-instruments.in / info@cem-india.com
Web: www.cem-instruments.in / www.cem-india.com

CEM INSTRUMENTS HEADQUARTER & FACTORY

19th Building, 5th Region, Baiwangxin Industry Park,
Songbai Road, Baimang, Xili, Nanshan, Shenzhen,
China, 518108
Tel: +86-755-27353188, Fax: +86-755-27653699

